

Portable refrigerators



DESCRIPTION

- Specially designed for transportation of blood and organs
- Possibility to be powered by D.C. current from ambulances and cars
- Compact, elegant and practical
- High quality of insulation for reduced power consumption
- Integrated lock provides good product safety

Characteristic

- **STRUCTURE** Realized in an environment-friendly atoxic plastic material (inside and outside)
- **INSULATION** Foamed polyurethane
- **THERMOSTAT** Digital electronic thermostat with audible and visual alarm (not for power failure)
- **HANDLES** Made in PVC, sidemounted, retractable
- **OPERATION** Compressor
- **KEY LOCKING** standard fitted
- **INTERNAL LIGHTING** standard fitted
- **OPTIONS** 230 V - 12 V Automatic feeder
Temperature chart recorder


C 29

C 41

C 65

Technical data	C - 29	C - 41	C - 65
Capacity	29 litres	41 litres	65 litres
Blood bag capacity (450ml)	18-20		45-48
Temperature	+10 °C / -10 °C		+10 °C / -20 °C
Absorption	0,048kW		0,067kW
Refrigerant	R600a		
Weight	16 kg	17 kg	24 kg
Supply	12V-24V 110V-240V/1~/50-60Hz		
External (WxDxH) dimensions	53 x 35 x 39 cm	60 x 37 x 40 cm	70 x 44 x 47 cm
Internal (WxDxH) dimensions (+additional compartment)	27,5x26x30,5 cm 15,5x26x11	37x28,5x30 cm 15x28,5x12,5	47x37,5x35 cm 15x37,5x17